

For Residential, Commercial and Industrial Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

Series LF3L, LF53L Poppet Type Pressure Relief Valves for Protection Against Excessive Pressure

Sizes: LF3L: 3/4" (20mm) LF53L: 1/2" (15mm)

Series LF3L and LF53L are used for protection against excessive pressure on domestic storage tanks or tankless water heaters. Similar in construction to Watts Model LF10L, the Model LF3L has no temperature relieving element. Model LF53L has the same basic design as Model LF3L except it is furnished in 1/2" (15mm) size and does not comply with ASME requirements. Pressure range is 75-150psi (5.2-10.3 bar). Series LF3L and LF53L come in standard settings of 75, 100, 125 and 150psi (5.2, 6.9, 8.6 and 10.3 bar). These Pressure Relief Valves are popularly used in conjunction with the Model LF210 gas shutoff valve on gas water heaters to shut off gas to heater if water heater temperature exceeds 210°F (99°C). The LF3L and LF53L features Lead Free* construction to comply with Lead Free* installation requirements.

Features

- Lead Free* cast copper silicon alloy bodies
- Furnished with test levers
- Relieves excessive pressure on storage tanks
- Relieves excessive pressure on tankless water heaters
- Model LF3L is ASME approved
- Model LF53L is CSA certified and is furnished in 1/2" size
- Compatible with Model LF210 gas shutoff valves

Models

Model LF3L ASME construction/Tested, listed and certified by the National Board of Boiler and Pressure Vessel Inspectors

Model LF53L Does not comply with ASME requirements Listed and certified by CSA

Model LF53 Model 53L without test lever



LF3L



LF53L

Materials

Body: Lead Free* cast copper silicon alloy
Spring: Stainless steel
Disc: Silicone

Pressure

Pressure range: 75-150psi (5.2-10.3 bar)
Standard settings: 75, 100, 125 and 150psi
(5.2, 6.9, 8.6 and 10.3 bar)

NOTICE

On all the above pressure relief valves, pressure setting should be not less than 25-30 lbs. above the maximum service main pressure.

Dimensions-Weights

MODEL	SIZE		HEIGHT		WIDTH		WEIGHT		VERSION
	in	mm	in	mm	in	mm	lbs.	gms.	
LF3L	3/4	20	3 1/2	89	1 3/4	44	5/8	284	M7
LF53L	1/2	15	3 1/2	89	1 7/8	48	1/2	227	M7

Model LF3L 3/4" (20mm) size CSA and ASME

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

ISO 9001-2008
CERTIFIED



USA: Tel. (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com
Canada: Tel. (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca

ES-LF3L-LF53L 1324

WATTS®

A Watts Water Technologies Company

© 2013 Watts